

# MultiMix D - MM30E

Digital Magnetic Stirrer Multiplace without Heating



Digital magnetic stirrer multiplace without heating, controlled by microprocessor.

- Module consisting of 3 stirring units in a single platform, with a single electrical connection. Each magnetic stirrer works independently.
- Adjustable stirring speed, controlled by microprocessor.
- Suitable for cinematic viscosity up to 40 cSt.
- Constant speed independently that the conditions of the sample vary.
- Smooth and progressive start to maintain the magnetic coupling, independently of the selected speed.
- Digital Display LCD backlighted indicating the selected and actual speed and timer (audible alarm).
- Membrane push-button control.
- Automatic restart after unexpected shut down keeping the same parameters as before the incident. An incident sign appears on the display.
- Antiscratch surface.
- Packaging: 63x32x22cm

## Technical Specifications:

Model	MM30E
Reference	10000-01046
Nº places	3
<b>Magnetic Stirring</b>	
Max. Volume (L) (x place)	8
Power (W) (x place)	12
Speed range (rpm)	200-1500
Resolution (rpm)	20
Timer (min)	0-120
<b>General Data</b>	
Plate Material	Stainless steel AISI 304
Plate Diameter (mm)	170x170 (x place)
Dimensions (mm)	525x205x70
Weight (kg)	6
Protection IP	IP43

Accesories	Reference
<b>Support Rod</b> Includes 2 fastening wing nuts to fix it. 450 mm	20000-00036
<b>Set of 18 assorted magnets</b>	20000-00026
<b>Stirring magnet 8x30mm * (pack 5)</b> *for other sizes, ask	20000-00008

