

Orbital Mini

Digital Orbital Shaker



Digital orbital shaker, controlled by microprocessor.

- Orbital shaker, suitable for medium or small containers.
- Speed adjustable, controlled by microprocessor.
- Constant speed independently of the load.
- Smooth and progressive start and stop, independently of the selected speed.
- Digital Display LCD backlighted indicating the selected and actual speed and timer (with audible alarm).
- Membrane push-button control.
- Automatic restart after unexpected shut down keeping the same parameters as before the incident. An incident sign appears on the display.
- Non-slipping surface.
- Quiet operation, suitable for continuous running.
- Packaging: 34x49x21cm

Technical Specifications:

Model	OS10E
Reference	10000-01010
Shaking	
Max. Load (Kg)	5
Power (W)	50
Type of Movement	Orbital
Amplitude (mm)	10
Speed Range (rpm)	50-500
Resolution (rpm)	5
Timer (min)	0-120
General Data	
Plate Material	Non-slipping surface
Useful surface (mm)	174x256
Dimensions (mm)	220x370x135
Weight (kg)	5,5
Protection IP	IP54

Accessories	Reference
Universal Platform mini 180x262mm with 4 rollers For shake vessels, erlenmeyers, flasks, tube racks, etc.	20000-00055
Set of 2 fastening springs To fix different vessels	20000-00043

